

**5a - DOOR HEAD SECTION**  
SCALE 1 : 2


\* FOR STUD FIXING DETAILS  
REFER TO TYPICAL TOP HAT FIXING  
DETAILS PACKAGE  
\*\* NON-COMBUSTIBLE PACKERS OR  
TOP HAT CLEAT SYSTEM AS REQUIRED

\*\*\* CAVITY FIRE BARRIER TYPE AND INSTALLATION  
TO MEET CAVITY SIZE REQUIREMENTS  
AND SUPPLIERS GUIDELINES  
\*\*\*\* DESIGNERS TO ASSESS REQUIREMENTS FOR  
SLOTTED HOLE PANEL FIXING TO ADDRESS  
THERMAL PERFORMANCE

## NOTES:

### Specifications

000-AC-GF-DWG-0101, 0102, 0103,  
0104, 0105, 0107, 0108, 3011



### Detail 5

000-AC-GF-DWG-3201

### LEGEND:

	EXISTING STRUCTURE NOT SUBJECT TO REMEDIAL WORKS
	APPROXIMATE LOCATION OF EXISTING WALL CLADDING
1:2	0 20 40 60 80 100mm

TITLE	DOOR HEAD DETAIL 5a		
CLADDING	SOLID ALUMINIUM		
SUBSTRATE	STEEL FRAMING	Rev	
DWG NUMBER	000-AC-GF-DWG-3250	8	