

DESIGNERS TO VERIFY  
COMBUSTIBILITY OF EXISTING  
INSULATION AND PROPOSE  
REMEDIAL ACTIONS

DESIGNERS TO VERIFY STUD  
LOCATIONS PRIOR TO DESIGN  
COMMENCEMENT

EXISTING STEEL  
STUD FRAMING

SARKING

NOMINAL 112X15mm  
TOP HAT \*\*

NOMINAL 135X35mm  
TOP HAT

SELF-TAPPING SCREWS

BONDED LAMINATE PANEL

SEALANT &  
BACKING ROD

EXISTING WINDOW

ISOLATION TAPE  
BETWEEN STEEL &  
ALUMINIUM SURFACES

RIVET OR SCREW  
ALUMINIUM PANEL  
TO CLIP

10-20

INTERNAL

12-15

VERTICAL CLOSED STATE  
CAVITY FIRE BARRIER \*\*\*

NOMINAL 135X35mm TOP HAT  
ABOVE AND BELOW THE  
WINDOW \*\*

ALUMINIUM Z-ANGLE  
BONDED TO BACK OF PANEL

20

EXTERNAL

## 1a - WINDOW JAMB SECTION

SCALE 1 : 2

\* FOR STUD FIXING DETAILS  
REFER TO TYPICAL TOP HAT FIXING  
DETAILS PACKAGE


\*\* NON-COMBUSTIBLE PACKERS OR  
TOP HAT CLEAT SYSTEM AS REQUIRED

\*\*\* CAVITY FIRE BARRIER TYPE AND INSTALLATION  
TO MEET CAVITY SIZE REQUIREMENTS  
AND SUPPLIERS GUIDELINES

## NOTES:

### Specifications

000-AC-GF-DWG-0101, 0102, 0103,  
0104, 0105, 0107, 0108, 6011



### Detail 1

000-AC-GF-DWG-6201


### LEGEND:



EXISTING STRUCTURE  
NOT SUBJECT TO  
REMEDIAL WORKS



APPROXIMATE LOCATION OF  
EXISTING WALL CLADDING



TITLE WINDOW JAMB DETAIL 1a

CLADDING BONDED LAMINATE

SUBSTRATE STEEL FRAMING

Rev

DWG NUMBER 000-AC-GF-DWG-6210

3